# Simple Notes Rewards

#32169 2 DESIGNS in 2 sizes

# MATERIALS



#### **Isacord Thread Colors**

0020 Black

0311 Canary

2152 Heather Pink

5912 Erin Green

\* Project instructions included after design list.

Note: One spool of 1000 meter thread is adequate for the project unless otherwise noted.

# MATERIALS



Note: Some designs in this collection may have been created using unique special stitches and/or techniques. To preserve design integrity when rescaling or rotating designs in your software, always rescale or rotate designs using the handles directly on-screen.



#### 32169-01 Thinking of You Card

Size Inches:	Size mm:	Stitch Count:
	158.8 X 117.5 mm 177.8 X 127.0 mm	3902 St. 4388 St.
1. Card Placer	2152	
2. Pink Detail.		2152
3. Yellow Deta	0311	
4. Black Detail		0020



#### 32169-02 Lucky Card

Size Inches:	Size mm:		Stitch Count:
6.25 X 4.62 in. 7.00 X 5.00 in.			
1. Card Placer	5912		
2. Green Deta	5912		
3. Black Detail	0020		

# MATERIALS



#### **Stabilizers**

- OESD StabilStick TearAway
- OESD Fuse and Seal CutAway
- OESD Medium Weight TearAway

#### Fabrics/Textiles

- Start Here Embroidery Blanks by OESD Greeting Card size A7 (5" x 7") folded
- Start Here Embroidery Blanks by OESD Greeting Card size A6 (4.5" x 6.25") folded

#### **Notion & Tools**

- OESD Expert Embroidery Tape TearAway
- OESD Fuse and Seal
- Embroidery Needle Sharp 75/11

#### **Isacord Thread Colors**

· Per thread chart



#### Notes

The card instructions, included in the collection, are general instructions.
For demonstration purposes, a sample card design that best demonstrates the technique is shown.
Thread requirements will vary by design.

#### Step 1

Hoop a piece of StabilStick TearAway paper side up.



#### Step 2


Score with scissors or a pin and remove paper to reveal adhesive.





#### Step 3

- Load selected design into the machine.
- Design in the example is from the collection, Stitched Sentiments -12874-01L.
- Thread the machine per the thread chart.
- Stitch Machine Step 1, Card Placement Guide.



#### Step 4

• Place the front of the card face up within the placement stitch, lining up all edges.



### Step 5

• Stitch the remaining machine steps, per thread chart.





#### Step 6

- Remove the card and stabilizer from the hoop. Place the card face down and fold the stabilizer towards the card. Carefully cut the stabilizer away, close to the stitching.
- Note: Cutting the excess TearAway stabilizer will prevent creasing and bending the cardstock.



#### Step 7

• Cut coordinating cardstock paper (or scrapbook paper) slightly smaller than the front of the card. Cut a piece of Fuse and Seal to fit. Following the package instructions, iron the Fuse and Seal to the wrong side of the cardstock (scrapbook paper).



#### Step 8

 Remove paper from Fuse and Seal, line up card over the back side of card and iron to adhere.





Step 9


Your card is complete. Enjoy!





#### Step 1


- 2 cards folded to 5" x 7"
- Cut one card in half on the fold.
- Note: Instruction uses designs not included in this collection.





#### Step 2

- Load selected design into themachine.
- Design in the example is 51246-01L, Scissortail collection Cheeky Cards.
- Thread the machine per the threadchart.
- Hoop 1 piece of OESD Medium Weight TearAway stabilizer.
- Stitch Machine Step 1, Card Placement Guide.





#### Step 3

- Place 5" x 7" piece of cardstock within the Card Placement Line, lining up all edges.
- Tape in place.
- Note: Expert Embroidery Tape TearAway will not leave residue on the paper or tear the cardstock.



#### Step 4

• Stitch the remaining machine steps, per thread chart.





#### Step 5

- Remove the card and stabilizer from the hoop.
- Place the card face down and fold the stabilizer towards the card.
- Carefully cut the stabilizer away, close to the stitching.
- Note: Cutting the excess TearAway stabilizer will prevent creasing and bending the cardstock.





#### Step 6

• Cut 1 piece of Fuse and Seal slightly smaller than the size of your card.





#### Step 7

• Following the package instructions, iron the Fuse and Seal to the wrong side of the embroidered card.



#### Step 8

• Once cool, remove the paper backing.



## Step 9

- Place the embroidered half of the card over the front of the second card and fuse with a medium warm iron.
- The back of the embroidery is now hidden.







• The card is now complete. Enjoy!

