

MATERIALS



Isacord Thread Colors

2532 Pretty in Pink

3331 Cadet Blue

5220 Silver Sage

6011 Tamarack

Note: One spool of 1000 meter thread is adequate for the project unless otherwise noted.

MATERIALS



Stabilizers

OESD AquaMesh Plus

Fabrics/Textiles

 A finished corner, such as one on a napkin or tablecloth, is an ideal item to add your Tula Pink Freestanding Lace Corner to!

Notion & Tools

- OESD Grippy Grid
- OESD Perfect Scoring Tool
- OESD Expert Embroidery Tape WashAway
- OESD Perfect Embroidery Press Cloth
- Embroidery Needles Ballpoint 80/12

Isacord Thread Colors

· Per thread chart

SUMMARY



80396-01



Design Size: 6.99 X 5.77 in.

80396-02



Design Size: 6.93 X 5.27 in.

80396-03



Design Size: 6.90 X 5.40 in.

80396-04



Design Size: 6.61 X 5.65 in.



General Instructions

The freestanding lace (FSL) instructions, included in the collection, are general instructions. For demonstration purposes, a sample design that best demonstrates the technique is shown. Design 80396-01 is shown here. Thread requirements will vary by design, but the general technique is the same.

All designs are stitched with matching thread, top and bobbin.

NOTE: Some thread colors in the instructions have been changed or digitally enhanced for better visibility.

Step 1

• Using the OESD Grippy Grid, hoop one layer of AquaMesh Plus paper (shiny) side up for all designs.






Step 2

- Use the OESD Perfect Scoring Tool to score the paper.
- Remove the paper to reveal the adhesive surface.




Step 3

- Load the selected design into the machine.
- Example design is 80396-01.
- Thread the machine per the thread chart.
- Place the hoop on the machine.
- Stitch Machine Step 1, Corner Placement Stitch.



Step 4

- Remove the hoop from the machine, but NOT the project from the hoop.
- Place the hoop on a flat surface.
- Place the corner (napkin, tablecloth, etc.), face up, aligned with the placement stitch.
- Finger press to secure.
- Tip: The Grippy Grid lines can assist with centering the corner.





Step 5

- Return the hoop to the machine.
- Stitch Machine Step 2, Cut Line and Tackdown.



Step 6

- Remove the hoop from the machine, but NOT the project from the hoop.
- Trim the corner (napkin, tablecloth, etc.) as close to the cut line as possible. If the outermost stitches (cut line) are cut, the inner stitches (tackdown) will hold the applique in place.
- Note: Be sure to trim on the side that will cut away just the corner and leave the body of the project intact.
- Tip: If the stabilizer is cut or a hole is created while trimming the fabric, use OESD Expert Embroidery Tape WashAway as a patch.





Step 7

- Return the hoop to the machine.
- Stitch the remaining machine steps per the thread chart with matching bobbin thread.



Step 8

- When the design is complete, remove the project from the hoop.
- Trim the stabilizer 1/4" 1/2" outside the design.



Step 9

- Rinse in warm running water until the design is only slightly tacky.
- Place right side down on a non-stick surface to dry.
 Parchment paper or a cooling rack work well. Dry completely.
- Once dry, press right side down on an OESD Perfect Embroidery Press Cloth.
- Tip: Wash the item in a garment or mesh bag with a clothes washer. It will require a good pressing after washing, but this method is quick and convenient!





Step 10

The project is complete. Enjoy!

