



MATERIALS



Isacord Thread Colors

0010 Silky White

1514 Brick

1725 Terra Cotta

2510 Roseate

2912 Sugar Plum

4220 Island Green

4423 Marine Aqua

5510 Emerald

5515 Kelly

Note: One spool of 1000 meter thread is adequate for the project unless otherwise noted.

MATERIALS



Stabilizers

Lightweight TearAway

Fabrics/Textiles

- (2) 5 1/2" x 6 1/2" White Felt (Per tag)
- (1) 5 1/2" x 6 1/2" OESD Clear Vinyl (Per tag)

Notion & Tools

- OESD Grippy Grid
- OESD Expert Embroidery Tape TearAway
- OESD Perfect Punch Tool
- OESD MiniMAT
- 1/4" x 10" Ribbon (1 per tag)

Isacord Thread Colors


Per the thread chart

SUMMARY













General Instructions


The instructions, included in the collection, are general instructions. For demonstration purposes, a sample design that best demonstrates the technique is shown. Design PK10087-01 is shown here.


Fabric and thread requirements will vary by design, but the general technique is the same.

NOTE: Some thread colors in the instructions have been changed or digitally enhanced for better visibility.

Step 1

• Adhere one layer of StabilStick CutAway to the wrong side of the white felt to provide stiffness to the finished tag.








Step 2

 Using the OESD Grippy Grid, hoop one layer of Light Weight TearAway for all designs.



Step 3

- Load the selected design into the machine.
- Example design is PK10087-01.
- Thread the machine per the thread chart.
- Place the hoop on the machine.
- Stitch Machine Step 1, Front White Felt Placement Stitch.



Step 4


- Remove the hoop from the machine, but NOT the project from the hoop.
- · Place the hoop on a flat surface.
- · Completely cover the placement stitch with white felt.
- Tape in place with OESD Expert Embroidery Tape TearAway to secure.





Step 5

- Return the hoop to the machine.
- · Stitch Machine Step 2, Felt Tackdown.



Step 6

Match bobbin to thread and stitch Machine Steps 3 – 5.



Step 7

- Remove the hoop from the machine, but NOT the project from the hoop.
- Place the hoop on a flat surface.
- Turn the hoop over and place the white felt, right side up, completely covering the placement stitch.
- Carefully tape in place to secure.
 Tip: Avoid pushing too hard on the stabilizer to prevent it from dislodging from the hoop.





Step 8

- · Return the hoop to the machine.
- Stitch Machine Step 6, Back White Felt Tackdown.



Step 9

- Remove the hoop from the machine, but NOT the project from the hoop.
- Place the hoop on a flat surface.
- Turn the hoop over and place the clear vinyl completely covering the placement stitch.
- Carefully tape on the corners to secure.
 Tip: Avoid pushing too hard on the stabilizer to prevent it from dislodging from the hoop.



Step 10

- Return the hoop to the machine.
- Stitch Machine Step 7, Clear Vinyl Tackdown.
- Stitch Machine Step 8, Tag Cut Line.





Step 11

- When the design is complete, remove the project from the hoop.
- Trim just inside the Tag Cut Line.



Step 12

- Using the OESD MiniMat and OESD Perfect Punch Tool with the 3mm tip create the eyelet indicated in the diagram.
- Reference the Punch Tool Guides on page 10.
 Tip: Take care to not cut the stitching.



Step 13


- Insert a card in the back of the tag and secure it in place with a ribbon through the punched hole.
- The project is complete. Enjoy!



PUNCH TOOL GUIDES O



PK10087-01




PK10087-02



PK10087-03



PK10087-04



- = 2 MM
- = 3 MM
- = 4 MM