

Felt Veggie Pals

#PK50006 10 DESIGNS

MATERIALS



Isacord Thread Colors

0010 Silky White 0020 Black

0221 Light Brass

0870 Muslin

0873 Stone

1141 Tan 1220 Apricot

1252 Dark Tan

1301 Paprika

1312 Burnt Orange

1521 Flamingo

1904 Cardinal

2011 Fire Engine

2022 Rio Red

2160 Iced Pink

2506 Cerise

2674 Steel

5422 Swiss Ivy

5510 Emerald

5643 Green Dust

5730 Apple Green

* Project instructions included after design list.

Note: One spool of 1000 meter thread is adequate for the project unless otherwise noted.

MATERIALS



Stabilizers

- OESD PolyMesh CutAway
- OESD Top Cover Permanent Topping Variety Pack
- OESD Applique Fuse and Fix
- OESD Fuse and Seal (1/4" by width of the opening)

Fabrics/Textiles

- Assorted colors felt
- Small Sizes:

Fabric body (2) 6" x 9" Applique (1) 5" x 5" · Large Sizes:

Fabric body (2) 9" x 12" Applique (1) 6" x 6"

Note: Fabric sizes are estimates and may result in overage.

Notion & Tools

- OESD Expert Embroidery Tape TearAway
- OESD Expert Point and Press Tool
- OESD Perfect Embroidery Press Cloth
- Alligator Clamps
- Embroidery Needle Sharp Size 75/11
- Fiberfill stuffing

Isacord Thread Colors

Per thread chart



General Instructions

The Veggie Pal instructions included in the collection are general instructions. For demonstration purposes, a sample design that best demonstrates the technique is shown. Fabric and thread requirements will vary by design.

Note: Some thread colors in instructions have been changed or digitally enhanced for better visibility.

Step 1

- Print the mirrored version of the required templates (100% or 1:1 ratio) onto the paper side of Applique Fuse and Fix.
- Roughly cut out each template about a 1/4" outside of the line.



- Fuse the trimmed templates to the back of the appropriate applique fabric with the paper side of the printed template up.
- Hold the iron on the template for 10-15 seconds for a secure fuse.





Step 3

- Trim the prepared appliques precisely on the outer edge of the black outline.
- Set aside.



Step 4

- · Hoop one layer of PolyMesh CutAway.
- · Load selected design into the machine.
- Design in the example is PK50006-03S.



- · Thread the machine per the thread chart.
- · Place the hoop on the machine.
- Stitch Machine Step 1, Purple Felt Placement Stitch.





Step 6

- Remove the hoop from the machine, but NOT the project from the hoop.
- Place the hoop on a flat surface.
- Place one piece of purple felt right side up, completely covering the placement stitch.
- Tape in place to secure.



Step 7

- Return the hoop to the machine.
- Stitch Machine Step 2, Tackdown.



- Stitch Machine Step 3, Green Felt Placement Stitch.
- Remove the hoop from the machine, but NOT the project from the hoop.
- Place on a flat surface.





Step 9

- Remove the paper from the back of the prepared applique to expose the adhesive
- Position the applique, fabric side up, within the placement stitch, matching the cut edges with the stitching line.
- Finger press to secure.
 Note: Applique Fuse and Fix is repositionable.



Step 10

- Return the hoop to the machine.
- · Stitch Machine Step 4, Tackdown.



- Remove the hoop from the machine, but NOT the project from the hoop.
- · Cover the face area with a top cover.
- Tape in place to secure.
- Note: Top Cover is used for a better-quality cover stitch on felt.
- Match the Top Cover to the thread color as closely as possible.
- EX. Black thread is used for the eyes; use a black Top Cover.





Step 12

- Return the hoop to the machine and stitch Machine Steps 5-8 per the thread chart.
- STOP before Machine Stitch 9, Seam Stitch/Match Fabric.
- Remove the hoop from the machine, but NOT the project from the hoop.
- · Place on a flat surface.
- Remove as much of the excess Top Cover as you can by gently tearing it away.



Step 13

- Place the second piece of purple felt right side down directly over the first piece.
- Tape in place to secure.



___Step 14

- · Return the hoop to the machine.
- · Stitch Machine Step 9, Seam Stitch/Match Fabric.





Step 15

- Remove the hoop from the machine and the project from the hoop.
- Trim approximately 1/4" from the seam stitch.
- DO NOT cut off the "neck" opening.
- Trim across the opening above the vertical lines of stitching.
- Clip each inner corner of the neck to, but not through, the corner stitch.
- · Clip curves as needed for easier turning.



Step 16

- · Turn the project right side out.
- Use the large end of the Expert Point and Press Tool to help push out the corners, curves, and sides.



- Use OESD Alligator Clamps to stuff the Veggie Pal with polyester fiberfill.
 - NOTE: For a smooth project, use small amounts of fiberfill instead of large pieces. The larger pieces appear lumpier.





Step 18

- Press the seam allowance into the opening.
- Place a small piece of Fuse and Seal inside and press to seal the opening, following the manufacturer's instructions.
- · Let cool completely.
- The neck opening is now permanently closed.



Step 19

• The project is complete. Enjoy.









































